

PHILIPS



EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	CRI	K	Levensduur
64721600	Master LED tube 1200mm UO 15.5W G13 T8 230V	36W	15,5W	2300	160°	83	3000	50000u
64723000	Master LED tube 1200mm UO 15.5W G13 T8 230V	36W	15,5W	2500	160°	83	4000	50000u
64727800	Master LED tube 1500mm UO 23W G13 T8 230V	58W	23,0W	3400	160°	83	3000	50000u
64729200	Master LED tube 1500mm UO 23W G13 T8 230V	58W	23,0W	3700	160°	83	4000	50000u
64731500	Master LED tube 1500mm UO 23W G13 T8 230V	58W	23,0W	3700	160°	83	6500	50000u
69747400	Master LED tube 600mm HO 8W G13 T8 230V	18W	8W	1000	160°	83	3000	50000u
69749800	Master LED tube 600mm HO 8W G13 T8 230V	18W	8W	1050	160°	83	4000	50000u
68708600	Master LED tube EM 900mm HO 12W G13 T8 230V	30W	12W	1575	160°	83	4000	50000u
59235600	Master LED tube EM 1200mm HO 12,5W G13 T8 230V	36W	12,5W	2000	160°	80	3000	50000u
59237000	Master LED tube EM 1200mm HO 12,5W G13 T8 230V	36W	12,5W	2100	160°	80	4000	50000u
59241700	Master LED tube EM 1500mm HO 18,2W G13 T8 230V	58W	18,2W	2900	160°	80	3000	50000u
59243100	Master LED tube EM 1500mm HO 18,2W G13 T8 230V	58W	18,2W	3100	160°	80	4000	50000u
59245500	Master LED tube EM 1500mm HO 18,2W G13 T8 230V	58W	18,2W	3100	160°	80	6500	50000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	CRI	K	Levensduur
71103300	CorePro LED tube EM 600mm 8W G13 230V	18W	8,0W	800	240°	80	4000	30000u
71107100	CorePro LED tube EM 1200mm 14,5W G13 230V	36W	14,5W	1600	240°	80	4000	30000u
71091300	CorePro LED tube EM 1500mm 20W G13 230V	58W	20,0W	2200	240°	80	4000	30000u
80166600	CorePro LED tube UN 1200mm HO 18W G13 T8 230V	36W	18,0W	1850	240°	80	3000	30000u
80168000	CorePro LED tube UN 1200mm HO 18W G13 T8 230V	36W	18,0W	2000	240°	80	4000	30000u
80172700	CorePro LED tube UN 1500mm HO 23W G13 T8 230V	58W	23,0W	2500	240°	80	3000	30000u
80174100	CorePro LED tube UN 1500mm HO 23W G13 T8 230V	58W	23,0W	2700	240°	80	4000	30000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Dimbaar	CRI	K	Levensduur
71382200	TrueForce LED 110-88W E40 100-145V 120D HPI vervanger	HPL/HPI/SON 250W	88W	11000	--	80	4000	50000u
59678100	TrueForce LED 120-100W E40 230V 120D HPI vervanger	HPL/HPI/SON 250W	100W	12000	--	80	4000	50000u

# CEBEO RUNNERS LED LAMPEN

OP VOORRAAD BIJ CEBEO

2021



**74273000**  
Classic LED bulb A60 7W 60W  
E27 2700K 806lm CRI80 15000u  
vanaf € 2,00



**77329800**  
Classic LED bulb A60 Dim 7.2W 60W 270°  
E27 2700K 806lm CRI80 15000u  
vanaf € 2,50



**57755400**  
CorePro LED bulb A60 8W 60W 200°  
E27 2700K 806lm CRI80 15000u  
vanaf € 1,50

PHILIPS

cebeo  
A Sonepar Company

cebeo  
A Sonepar Company

# CEBEO RUNNERS LED LAMPEN

OP VOORRAAD BIJ CEBEO



EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
70755500	Master LED Expert Color dimbaar 3.9-35W GU10 230V	35W	3,9W	265	36°	•	97	2700	40000u
70757900	Master LED Expert Color dimbaar 3.9-35W GU10 230V	35W	3,9W	280	36°	•	97	3000	40000u
70767800	Master LED Expert Color dimbaar 5.5-50W GU10 230V	50W	5,5W	355	36°	•	97	2700	40000u
70769200	Master LED Expert Color dimbaar 5.5-50W GU10 230V	50W	5,5W	375	36°	•	97	3000	40000u
70771500	Master LED Expert Color dimbaar 5.5-50W GU10 230V	50W	5,5W	400	36°	•	97	4000	40000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
70773900	Master LED spot VLE dimbaar 3.7-35W 2700K GU10 230V	35W	3,7W	260	36°	•	90	2700	25000u
70775300	Master LED spot VLE dimbaar 3.7-35W 3000K GU10 230V	35W	3,7W	270	36°	•	90	3000	25000u
70785200	Master LED spot VLE dimbaar 4.9-50W 2700K GU10 230V	50W	4,9W	355	36°	•	90	2700	25000u
70787600	Master LED spot VLE dimbaar 4.9-50W 3000K GU10 230V	50W	4,9W	365	36°	•	90	3000	25000u
70789000	Master LED spot VLE dimbaar 4.9-50W 4000K GU10 230V	50W	4,9W	380	36°	•	90	4000	25000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
72133900	CorePro LED spot dimbaar 4-35W GU10 230V	35W	4W	250	36°	•	80	2700	15000u
72135300	CorePro LED spot dimbaar 4-35W GU10 230V	35W	4W	260	36°	•	80	3000	15000u
72137700	CorePro LED spot dimbaar 5-50W GU10 230V	50W	5W	350	36°	•	80	2700	15000u
72139100	CorePro LED spot dimbaar 5-50W GU10 230V	50W	5W	365	36°	•	80	3000	15000u
73024900	CorePro LED spot dimbaar 5-50W GU10 230V	50W	5W	380	36°	•	80	4000	15000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
73883200	Master LED Expert Color dimbaar 6.5-35W GU5.3 12V	35W	6,5W	420	36°	•	97,0	2700	40000u
73885600	Master LED Expert Color dimbaar 6.5-35W GU5.3 12V	35W	6,5W	440	36°	•	97,0	3000	40000u

EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
81267900	Master LED spot LV dimbaar 8-50W GU5.3 MR16 12V	50W	8W	621	36°	•	80	2700	40000u
81269300	Master LED spot LV dimbaar 8-50W GU5.3 MR16 12V	50W	8W	621	36°	•	80	3000	40000u
70823100	Master LED spot VLE dimbaar 5.5-35W GU5.3 MR16 12V	35W	5,5W	450	36°	•	80,0	2700	25000u
70825500	Master LED spot VLE dimbaar 5.5-35W GU5.3 MR16 12V	35W	5,5W	460	36°	•	80,0	3000	25000u
81554000	Master LED spot VLE dimbaar 7-50W GU5.3 MR16 12V	50W	7W	621	36°	•	80	2700	25000u
81556400	Master LED spot VLE dimbaar 7-50W GU5.3 MR16 12V	50W	7W	630	36°	•	80	3000	25000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Dimbaar	CRI	K	Levensduur
57757800	CorePro LED bulb 5,5-40W E27 A60 230V	40W	5,5W	470	--	80	2700	15000u
57755400	CorePro LED bulb 8-60W E27 A60 230V	60W	8W	806	--	80	2700	15000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Dimbaar	CRI	K	Levensduur
77325000	Classic filament LED bulb dimbaar 5,5-40W E27 A60 230V	40W	5,5W	470	•	80	2700	15000u
63086700	Classic filament LED bulb 4,3-40W E27 A60 230V	40W	4,3W	470	--	80	2700	15000u
77329800	Classic filament LED bulb dimbaar 8-60W E27 A60 230V	60W	8W	806	•	80	2700	15000u
74273000	Classic filament LED bulb 7-60W E27 A60 230V	60W	7W	806	--	80	2700	15000u
64908100	Classic filament LED bulb 8,5-75W E27 A60 230V	75W	8,5W	1055	--	80	2700	15000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Dimbaar	CRI	K	Levensduur
57407200	Classic filament LED candle 2,25W E14 B35 230V	25W	2W	250	--	80	2700	15000u
77337300	Classic filament LED candle dimbaar 5-50W E14 B35 230V	40W	5W	470	•	80	2700	15000u
80853500	Classic filament LED candle 4,3-40W E14 B35 230V	40W	4,3W	470	--	80	2700	15000u



EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
68692500	Master LED spot LV dimbaar 11-50W G53 AR111 12V	50W	11W	560	24°	•	90	2700	40000u
51490000	Master LED spot LV dimbaar 11-50W G53 AR111 12V	50W	11W	580	24°	•	90	3000	40000u
68694900	Master LED spot LV dimbaar 11-50W G53 AR111 12V	50W	11W	550	40°	•	90	2700	40000u
68696300	Master LED spot LV dimbaar 11-50W G53 AR111 12V	50W	11W	570	40°	•	90	3000	40000u
68702100	Master LED spot LV dimbaar 15-75W G53 AR111 12V	75W	15W	800	40°	•	90	2700	40000u
68704500	Master LED spot LV dimbaar 15-75W G53 AR111 12V	75W	15W	810	40°	•	90	3000	40000u

EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
76852200	Master LED spot CLA dimbaar 6-50W E27 PAR20 230V	50W	6W	500	40°	•	80	2700	25000u
76854600	Master LED spot CLA dimbaar 6-50W E27 PAR20 230V	50W	6W	515	40°	•	80	3000	25000u
71374700	Master LED spot CLA dimbaar 6-50W E27 PAR20 230V	50W	6W	540	40°	•	80	4000	25000u

EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
52253000	CorePro LED linear 118mm 6,5-60W R7S 230V	60W	6,5W	806	360°	--	80	3000	20000u
57879700	CorePro LED linear 118mm dimbaar 14-100W R7S 230V	100W	14W	1600	360°	•	80	3000	15000u
71400300	CorePro LED linear 118mm dimbaar 14-120W R7S 230V	120W	14W	2000	360°	•	80	3000	15000u
64673800	CorePro LED linear 118mm dimbaar 17,5-150W R7S 230V	150W	18W	2460	360°	•	80	3000	15000u

EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
76761700	CorePro LED capsule LV 1-10W G4 12V	10W	1,0W	110	--	--	80	2700	15000u
76765500	CorePro LED capsule LV 1,8-20W G4 12V	20W	1,8W	205	--	--	80	2700	15000u
82694200	CorePro LED capsule LV 2,5-28W G4 12V	28W	2,5W	300	--	--	80	2700	15000u
76779200	CorePro LED capsule LV 1,8-20W GY6,35 12V	20W	1,8W	210	--	--	80	2700	15000u
73506700	CorePro LED capsule 3,5-40W G9 230V	40W	3,5W	400	--	--	80	2700	15000u
65780200	CorePro LED capsule 4,8-60W G9 230V	60W	4,8W	570	--	--	80	2700	15000u

EOC Code	Omschrijving	Traditioneel	LED	lm	Stralingshoek	Dimbaar	CRI	K	Levensduur
54127200	CorePro LED 6,5W G24D-2 PLC 230V	18W	6,5W	600	160°	--	83	3000	30000u
54129600	CorePro LED 6,5W G24D-2 PLC 230V	18W	6,5W	650	160°	--	83	4000	30000u
54123400	CorePro LED 8,5W G24D-2 PLC 230V	26W	8,5W	900	160°	--	83	3000	30000u
54125800	CorePro LED 8,5W G24D-3 PLC 230V	26W	8,5W	950	160°	--	83	4000	30000u
54119700	CorePro LED 6,5W G24Q-2 PLC 20-50V	18W	6,5W	600	160°	--	83	3000	30000u
54121000	CorePro LED 6,5W G24Q-2 PLC 20-50V	18W	6,5W	650	160°	--	83	4000	30000u
54115900	CorePro LED 9W G24Q-3 PLC 20-50V	26W	9W	900	160°	--	83	3000	30000u
54117300	CorePro LED 9W G24Q-3 PLC 20-50V	26W	9W	950	160°	--	83	4000	30000u

-- niet dimbaar/geen stralingshoek